



169.00 EUR
incl. 19% VAT, plus [shipping](#)

- GPS/GLONASS/GSM/4G/5G !
- WLAN / Bluetooth !
- Active antenna !
- SMA connectors !

Support:  [Specifications](#)

The Gar VFQ69383x21JN VFQ69383B21JN-518L multiport/multiband antenna provides an excellent solution for public safety, transportation, and aftermarket fleet applications. Configured for two-port operation over the 3G/4G/5G/ISM/CBRS bands and oneport operation over the low//high frequency Wi-Fi bands. An additional fourth port provides an active antenna for enabling GNSS global navigation services.

FEATURES AND BENEFITS

- One single-hole mount/fixing reduces vehicle damage and the cost of installation
- Attractive IP67 low profile aerodynamic housing
- Multiband/multiport operation with GNSS navigation
- Operates well on a ground plane and without a ground plane.

APPLICATIONS

- FirstNet/Public safety
- Transportation
- Aftermarket fleet

- 5G-ready
- Rugged LTE gateways
- Others

| | |
|---------------------------|---|
| Antennen Model | VFP69383B22JN-518J |
| Port Configuration | 2x 3G/4G/5G/ISM/CBRS, 2x WIFI |
| Watchdog | Watchdog Timer Support, Offer 1 – 255 Step |
| Operating Frequency (Mhz) | 698-806 / 824-894 / 880-960 / 1690-3800 / 2400-2500 / 4900-6000 |
| Azimuth Plane 3db | 360° Omnidirectional |
| Beamwidth | |
| Nominal IMpedance (ohms) | 50 |
| Polarization | Linear Vertical |
| Max Power - Ambient 25°C | 10 Watts |
| | Mechanical Secifications |
| Dimensions | 179x63x48 mm / 0,63 kg |
| CableType | LMR 100, Black |
| Mounting | P-Mount |
| Baseplate. | Aluminium |
| | Enviremental Specifications |
| Operating Enviroment | Outdoor Vehicle / IP67 |
| | Operating Temperature: -30 to +70°C |
| Temperatures | Storage Temperature: -40 to +85°C |
| Material Substance | |
| Compliance | RoHS |